



CO₂ capture by using hydrates: 4) From experimental evidences to economic impossibility as a post combustion process

Jean-Michel Herri, Matthias Kwaterski, Aurélie Galfré, Pedro Brantuas, Ana Cameirão, Yamina Ouabbas, Baptiste Bouillot, Anne Siquin, Paul Broutin, Ulrich Liebenthal, et al.

► To cite this version:

Jean-Michel Herri, Matthias Kwaterski, Aurélie Galfré, Pedro Brantuas, Ana Cameirão, et al.. CO₂ capture by using hydrates: 4) From experimental evidences to economic impossibility as a post combustion process. Ziran Zhong. The 8th International Conference on Gas Hydrates, Jul 2014, Pékin, China. pp.t4-13. <hal-01068274>

HAL Id: hal-01068274

<https://hal.archives-ouvertes.fr/hal-01068274>

Submitted on 25 Sep 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

CO₂ CAPTURE BY USING HYDRATES: 4) FROM EXPERIMENTAL EVIDENCES TO ECONOMIC IMPOSSIBILITY AS A POST COMBUSTION PROCESS

HERRI Jean-Michel(*) , KWATERSKI Matthias, GALFRE Aurélie, BRANTUAS, Pedro, CAMEIRAO Ana, OUABBAS Yamina, BOUILLOT Baptiste
Gas Hydrate Dynamics Centre, Ecole Nationale Supérieure des Mines de Saint-Etienne, 158 Cours Fauriel, 42023 Saint-Etienne, France, (*) corresponding author herri@emse.fr

SINQUIN, Anne, BROUTIN, Paul,
IFP Energies nouvelles, 1 et 4 avenue de Bois-Préau, 92852 Rueil-Malmaison France

LIEBENTHAL Ulrich, KATER Alfons
Hamburg University of Technology, Germany

ABSTRACT

The post-combustion CO₂ capture by using clathrates is a method which takes profit of the CO₂ selectivity in gas hydrate to separate it from nitrogen, or other exhausting gases from gas combustion or coal combustion. The bottleneck is the operative pressure which still remains high and needs to be drop down to 0.5 MPa in order to compete with the reference case using Amines. After two national projects (SECOHYA, ACACIA) and an European program (iCAP), we tested different classes of thermodynamic additives, organic ones (water non soluble cyclopentane, water soluble THF) which form classical gas hydrates with structure SII, and ionic ones (Tetra-N-Butyl Ammonium Bromide, TBAB) which forms new types of structures, and mixture of promoters. In this presentation, we present a flow-sheet for a CO₂ capture process, with two stages, a bulk and a finisher. After sizing, we emphasize that the volume of the bulk is similar to the volume of an Amine Process because the crystallization operates in a Gas/liquid transfer limitation regime. But, the volume of solvent to handle is much too large to be reasonable.

Keywords: semi clathrates hydrates, CO₂ capture, sizing, costing

INTRODUCTION

The main motivation for CO₂ capture via hydrates formation is a reduction of the heat duty, which strongly reduces the power plant efficiency when using an absorption processes with chemical solvent.

Nevertheless, hydrates formation requires high pressure levels and low temperatures in the absorber: so, flue gas conditioning is necessary. The principle of the design of the process (without flue gas conditioning) is shown in Figure 1. The main components are the vessel for hydrates formation, the vessel for hydrates dissociation and the slurry pump that transfers the hydrate slurry from the formation vessel to the dissociation one. Preliminary assumptions were the following:

- with appropriate additives, it is possible to operate hydrates formation at 5 bar and 0 °C,

- dissociation may be realised at 50 bar and 20 °C,
- the heat for dissociation does not affect the efficiency of the power plant, given that the temperature level is close to ambient conditions.




Figure 1: Design of the capture process with hydrates

To provide for the right flue gas conditions in the hydrates formation vessel (5 bars and 0 °C) three main steps are necessary:

- Compression;
- Drying (to avoid freezing);
- Cooling.

The drying is essential as surfaces in the heat exchanger of the last cooling stage have temperatures below the freezing point of water. Even if a temperature approach of 10 °C is used between flue gas and cooling medium, local freezing might still harm the components and affect the flow conditions in the heat exchanger.

Three different cooling strategies have been investigated and Figure 2 presents the variant with the lowest impact on the energy penalty of the power station.




Figure 2: Flow scheme of the flue gas conditioning section

Within this variant, the flue gas leaving the FGD unit is cooled by the clean gas leaving the hydrates formation column and is sent to the compression train. Only one intercooler is foreseen to reach a high temperature level downstream of the compression train. A high temperature level is required to heat up the clean gas before it enters the clean gas expander. Downstream of the second flue gas cooler and the liquid-water knock-off drum, the flue gas is dried in an adsorptive drying unit. The flue gas is then directly cooled using a flue gas expander. The backpressure of the expander is determined by the requirements for hydrates formation. The flue pressure at the outlet of the compression train can be varied to reach the desired temperature at the inlet of the hydrates formation column.

The energy penalty corresponding to this flue gas conditioning has been evaluated. For the CO₂

capture based on hydrate formation flue gas conditioning represents the largest contributor to the overall efficiency penalty. In this section all interface quantities of the flue gas conditioning (i.e., the electrical energy for pumps and compressors, the steam for the adsorptive drying unit, the cooling water pumps) and CO₂ compression are considered without taking into account any energy requirement for the capture unit itself (e. g. slurry pump). The break down of the corresponding efficiency penalty is shown in Figure 3.




Figure 3: Break down of the efficiency penalty for flue gas conditioning and the CO₂ compression (assumed CO₂ pressure at CO₂ compressor inlet = 50 bar)

The influence of the desired flue gas pressure in the hydrates formation column is shown in Figure 4. For a flue gas pressure above 15 bar, the energy penalty for flue gas conditioning is higher than energy penalty of a MEA based capture process unit (10 points). So, a capture process based on hydrate formation must be operated at a pressure under 15 bar in order to compete with a capture process based on chemical solvent.




Figure 4: Influence of the desired flue gas pressure on the efficiency penalty (desired flue gas temperature = 0 °C, assumed CO₂ pressure at CO₂ compressor inlet = 50 bar). The efficiency penalty does not include the capture process.

We propose here (see ANNEX) a flow sheet in two stages, a bulk reactor and a finisher. The bulk reactor operates with a gas phase at a mole fraction higher than 0.2 in order to form a pure CO₂ hydrate (see Figure 5 and Paper 1/4 of this series). The finisher captures the remaining CO₂ in order to meet the specifications, especially to recover CO₂ up to a fraction hereafter called RECOV.

The Liquid solution is TBAB solution at a weight fraction of $w_{TBAB}^L = 0.32$. It crystallizes a S38 structure (see paper 2/4 of this series) below a temperature of 10.38°C, corresponding to the eutectic point. The water and TBAB composition remains the same in the liquid and in the solid.

The Hard-Coal gas has been chosen as a base case flue gas for the design of the hydrate formation process. It is defined as:

- Flowrate (kg/s) 772.8
- Pressure (bara) 1.018
- Temperature(°C) 49
- Composition (wt.%): 67.26% N₂; 3.58% O₂; 20.58% CO₂; 7.43% H₂O; 1.14% Ar

The process will be designed with an overall 90% CO₂ removal efficiency, a typical CO₂ recovery in reference carbon dioxide capture and storage (Thambimuthu et al, 2005; Oexmann, 2012; Liebenthal, 2011)

DETAILS ON THE FLOWSHEET

The flow sheet is given in ANNEX.

The CO₂ mole fraction ($y_{CO_2}^{dry\ flue\ gas}$) of the Flue Gas after drying, the mole flow rate $F^{dry\ flue\ gas}$ remains lower than 0.2. So, a recycling of pure CO₂ (mole flow rate $F^{Recycling}$) is injected before entering the bulk in order to increase the CO₂ content so that the bulk reactor can operate at a CO₂ gas molar fraction of 0.2. It is a key point of the process to crystallize hydrate with 100% CO₂. The quantity of hydrate to crystallize is consequently increased. It brings a penalty from two points of view : 1) the slurry to handle at the exit of the bulk reactor is increased, 2) the size of the reactor is increased too.

$$F_{CO_2,hyd}^{OUT,bulk} = RECOV \cdot F^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas} + F^{Recycling} \quad (1)$$

OPERATIVE CONDITIONS OF THE BULK REACTOR

We recall here the numeric data and correlations given in the paper number 2/4 of this series of four papers.

The maximum gas storage capacity of the TBAB, 38H₂O structure is:

$$n_{S38,Max}^{STORAGE} = 3191\ mole.m^{-3} \quad (2)$$

The effective storage capacity takes into account the occupancy of cavities θ_j by component j. It depends on thermodynamics.

$$n_{S38,j}^{STORAGE} = \theta_j \cdot n_{S38,Max}^{STORAGE} \quad (3)$$

The Liquid solution is TBAB solution at a weight fraction of $w_{TBAB}^L = 0.32$. We can evaluate the mole number of water per volume of liquid solution:

$$n_{water,L}^{STORAGE} = 38954\ mole.m^{-3} \quad (4)$$

So, the Liquid storage capacity of gas components j is given by:

$$n_{j,L}^{STORAGE} = n_{water,L}^{STORAGE} x_{j,L} \quad (5)$$

$x_{j,L}$ [mole of component j / mole of water] is the solubility of the component j .

The equilibrium pressure is fixed by the difference of temperature between the operative temperature Θ_{Bulk} [°C] and the value of 10.38°C at which the pure TBAB semi-clathrate of structure S38 can form from a liquid solution at a TBAB mass fraction of 0.32. From the complete thermodynamic modeling, we have determined the operative pressure of a capture process $P_{Bulk,eq}$ [MPa] from the following correlation:

$$P_{Bulk,eq} = 3.687 \cdot 10^{-3} (\Theta_{Bulk} - 10.38)^3 - 7.839 \cdot 10^{-3} (\Theta_{Bulk} - 10.38)^2 + 2.035 \cdot 10^{-1} (\Theta_{Bulk} - 10.38) \quad (6)$$

The operative pressure cannot be lower than $P_{Bulk,eq} / y_{CO_2}^{Bulk}$ where $y_{CO_2}^{Bulk}$ is the average mole fraction of CO₂ in the gas phase of the bubble column. We assume the operative pressure to be higher and fixed by a coefficient q :

$$P_{Bulk} = q \cdot P_{Bulk,eq} / y_{CO_2}^{Bulk} \quad (7)$$

Also, the thermodynamic modeling has allowed determining the occupancy factor of the cavities, independently of the gas hydrate former.

$$\theta = -3.719 \cdot 10^{-3} (\Theta_{Bulk} - 10.38)^2 + 9.926 \cdot 10^{-1} (\Theta_{Bulk} - 10.38) \quad (8)$$

It is assumed that the bulk reactor operates in a Gas/liquid transfer limited regime. The temperature in the bulk reactor is Θ_{Bulk} [°C] and the corresponding equilibrium pressure of the pure CO₂ semi clathrate hydrate of TBAB is $P_{Bulk,eq}$ [MPa], given in Eq. 6:

$$x_{CO_2,L}^{OUT,Bulk} = \frac{\phi_{CO_2}^G P_{Bulk,eq}}{k_{H,CO_2,w}^{L_w} (T_{Bulk}, p_w^{o,\sigma})} \quad (9)$$

The values of the Henry constants $k_{H,j,w}^{L_w} (T, p_w^{o,\sigma})$ are retrieved from experimental values, or from correlations (Galfré et al, 2014). It is assumed that the solubility of gaseous

component into TBAB solution is similar to the solubility of gaseous components in pure water. $\phi_{CO_2}^G$ is the fugacity coefficient.

The bulk reactor is assuming to work at a CO₂ mole fraction $y_{CO_2,min}^{Bulk} = 0.2$. At such a composition, the semi-clathrate hydrate is a practically pure CO₂ hydrate (see paper 1/4 of this series of 4 papers). The other gas components are not consumed during the crystallization, and they are in physical equilibrium with the liquid phase at pressure P_{bulk} [MPa] given in Eq.7:

$$x_{j,L}^{OUT,Bulk} = \frac{y_j^{Bulk} \phi_j^G P_{Bulk}}{k_{H,j,w}^{L_w} (T_{Bulk}, p_w^{o,\sigma})} \quad (10)$$

The bulk and finisher reactors are considered as homogeneous reactions in which the crystallization rate is limited by the gas/liquid mass transfer. From paper 3/4 of this series, we showed that the volume of the reactor is given by:

$$V_L = \frac{r_{CO_2}}{\frac{k_L^{CO_2}}{d_b} 6 \frac{\epsilon_G}{1 - \epsilon_G} (x_{CO_2,ext} - x_{CO_2,bulk}) C_{H_2O}} \quad (11)$$

Where r_{CO_2} [mol.s⁻¹] is the rate of CO₂ capture in the hydrate phase (Eq.1)

$$r_{CO_2} = F_{CO_2,hyd}^{OUT,bulk} \quad (12)$$

Once the operative temperature is fixed, the equilibrium pressure is fixed (Eq. 6), and the occupancy of gas in the hydrate structure (Eq.8) is also fixed. So, we can evaluate the flow rate of hydrate to be handled from the rate of rate of gas, r_{CO_2} [mol.s⁻¹], which has been captured:

$$Q_{hyd}^{OUT,Bulk} = \frac{r_{CO_2}}{\theta_j \cdot n_{S38,Max}^{STORAGE}} \quad (13)$$

It is also possible to evaluate the liquid flow rate from the consideration that the slurry viscosity can not be too high. So the solid content can not exceed a value Φ_{MAX} (to be designed precisely) which can be around the value of $\Phi_{MAX} = 0.3$ (see paper 3/4 of this series).

$$Q_L^{OUT, Bulk} = \frac{1 - \Phi_{MAX}}{\Phi_{MAX}} Q_{hyd}^{OUT, Bulk} \quad (14)$$

FLUE GASES

The mole fraction of chemical species in the flue gases, dimensionless, is given by $y_i^{wet\ flue\ gas}$ and $y_i^{dry\ flue\ gas}$ respectively before and after the drying stage.

SPECIFICATIONS

RECOV is the CO₂ recovery ratio expressed as the ratio between the recovered molar flow rate ($F_{CO_2}^{OUT, BOTTOM}$) and the CO₂ molar flow rate in the

flue gas ($F^{wet\ flue\ gas} y_{CO_2}^{wet\ flue\ gas}$ or $F^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas}$)

$$RECOV = \frac{F_{CO_2}^{OUT, BOTTOM}}{F^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas}} \quad (15)$$




Figure 5 : Selectivity of the separation of CO₂ from N₂ during crystallization of semi-clathrate hydrates from TBAB solution, and comparison to the selectivity of clathrate hydrate of structure SI (Herri et al, 2014)

From the experimental results of Herri et al (2014) reported in Figure 5, it is assumed that the hydrates are filled with 100% CO₂ if the flue gas contains more than 20% CO₂

$$y_{CO_2} > 0.2 \Rightarrow z_{CO_2} = 1; \quad z_{other\ components} = 0 \quad (16)$$

If the gas phase is lower than 20% CO₂.

$$y_{CO_2} < 0.2 \Rightarrow z_{CO_2} = 5 \times y_{CO_2}; \quad z_{other\ components} = 1 - 5 \times y_{CO_2} \quad (17)$$

BOTTOM FLOW

The bottom flow gas is composed of pure CO₂

$$F_{CO_2}^{OUT, BOTTOM} = RECOV^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas} \quad (18)$$

TOP GAS

The top gas is composed of the non recovered CO₂ at a molar flow rate $F_{CO_2}^{OUT, TOP}$ and mole fraction $y_{CO_2}^{OUT, TOP}$. The *other components* are the component to be exhausted from the unit without being captured, mainly N₂, O₂, Ar and other components.

The TOP Gas CO₂ mole fraction can be easily determined. In fact

$$y_{CO_2}^{OUT, TOP} = \frac{F_{CO_2}^{OUT, TOP}}{F_{CO_2}^{OUT, TOP} + F_{other\ components}^{OUT, TOP}} \quad (19)$$

$F_{CO_2}^{OUT, TOP}$ corresponds to the non recovered CO_2 :

$$F_{CO_2}^{OUT, TOP} = (1 - RECOV) F^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas} \quad (20)$$

$F_{other\ components}^{OUT, TOP}$ corresponds to the gases which are not recovered in the CO_2 capture unit, and the flow rate is assumed to be flow rate in the flue gas :

$$F_{other\ components}^{OUT, TOP} = F^{dry\ flue\ gas} (1 - y_{CO_2}^{dry\ flue\ gas}) \quad (21)$$

$$y_{CO_2}^{OUT, TOP} = \frac{(1 - RECOV) y_{CO_2}^{dry\ flue\ gas}}{(1 - RECOV) y_{CO_2}^{dry\ flue\ gas} + (1 - y_{CO_2}^{dry\ flue\ gas})} \quad (22)$$

Finally, we can express the total top gas flow rate:

$$F^{OUT, TOP} = \frac{F_{CO_2}^{OUT, TOP}}{y_{CO_2}^{OUT, TOP}} = F^{dry\ flue\ gas} \left[\frac{(1 - RECOV) y_{CO_2}^{dry\ flue\ gas}}{(1 - RECOV) y_{CO_2}^{dry\ flue\ gas} + (1 - y_{CO_2}^{dry\ flue\ gas})} + (1 - y_{CO_2}^{dry\ flue\ gas}) \right] \quad (23)$$

RECYCLING FLOW

The bulk reactor is assumed to run with a minimum gas CO_2 mole fraction of $y_{CO_2, min}^{Bulk} = 0.2$.

In fact, at this concentration, it has been observed that the hydrate which is formed can be considered 100% CO_2 . Consequently, the feed gas entering the bulk reactor needs to be at higher concentration ($y_{CO_2}^{IN, Bulk} > y_{CO_2, min}^{Bulk}$) so that a reaction can be operated. The mole fraction in the feed gas ($y_{CO_2}^{dry\ flue\ gas}$) is probably at a lower concentration than $y_{CO_2}^{IN, Bulk}$ and the flow entering the bulk reactor needs to be completed with a recycling of pure CO_2 gas in order to reach the $y_{CO_2}^{IN, Bulk}$ value.

$$y_{CO_2}^{IN, Bulk} = \frac{F^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas} + F^{Recycling}}{F^{dry\ flue\ gas} + F^{Recycling}} \quad (24)$$

$$F^{Recycling} = F^{dry\ flue\ gas} \frac{y_{CO_2}^{IN, Bulk} - y_{CO_2}^{dry\ flue\ gas}}{1 - y_{CO_2}^{IN, Bulk}} \quad (25)$$

FINISHER REACTOR

CO_2 Mole Balance

$$F_{CO_2, Gas}^{OUT, Bulk} = F_{CO_2, hyd}^{OUT, Finisher} + F_{CO_2, L}^{OUT, Finisher} + F_{CO_2}^{OUT, TOP} \quad (26)$$

$F_{CO_2}^{OUT, TOP}$ is given from the process specification, following Eq.20, so:

$$F_{CO_2, Gas}^{OUT, Bulk} - F_{CO_2, hyd}^{OUT, Finisher} - F_{CO_2, L}^{OUT, Finisher} = (1 - RECOV) F^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas} \quad (27)$$

Other components Mole Balance

Other components are N_2, O_2 and Ar.

$$F_{other\ components, Gas}^{OUT, Bulk} = F_{other\ components, hyd}^{OUT, Finisher} + F_{other\ components, L}^{OUT, Finisher} + F_{other\ components}^{OUT, TOP} \quad (28)$$

$F_{other\ components}^{OUT, TOP}$ is given from the process specification, all the other components being not involved in the capture process:

$$F_{other\ components, Gas}^{OUT, Bulk} - F_{other\ components, hyd}^{OUT, Finisher} - F_{other\ components, L}^{OUT, Finisher} = (1 - y_{CO_2}^{dry\ flue\ gas}) F^{dry\ flue\ gas} \quad (29)$$

Relationship in between variables

The composition of the hydrate slurry is fixed by thermodynamic, and especially the ratio between CO_2 and other components. At gas CO_2 mole fraction lower than $y_{CO_2, min}^{Finisher} = 0.2$, we know from Eq.17 that:

$$\frac{F_{CO_2, hyd}^{OUT, Finisher}}{F_{other\ components, hyd}^{OUT, Finisher}} = \frac{5 y_{CO_2}^{OUT, TOP}}{1 - 5 y_{CO_2}^{OUT, TOP}} \quad (30)$$

Another relationship can be given of mole flow $F_{Gas}^{OUT, Bulk}$

$$\frac{F_{CO_2, Gas}^{OUT, Bulk}}{F_{other\ components, Gas}^{OUT, Bulk}} = \frac{y_{CO_2}^{Bulk}}{1 - y_{CO_2}^{Bulk}} \quad (31)$$

Also, we can give a relation between $F_{j,hyd}^{OUT,Finisher}$ and $F_{j,L}^{OUT,Finisher}$ for every components j, CO₂ and other components, because:

$$F_{j,hyd}^{OUT,Finisher} = Q_{hyd}^{OUT,Finisher} n_{S38,MAX}^{STORAGE} \theta_j \quad (32)$$

θ_j is the occupancy of cavities by component j.
So

$$Q_{hyd}^{OUT,Finisher} = \frac{F_{CO_2,hyd}^{OUT,Finisher}}{n_{S38,MAX}^{STORAGE} \theta_{CO_2}} \quad (33)$$

The volume liquid flow rate is given from Eq.14 by:

$$Q_L^{OUT,Finisher} = Q_{hyd}^{OUT,Finisher} \frac{1-\Phi}{\Phi}$$

And, finally, from Eq 5., Eq.33 and Eq.14, we can evaluate the mole flow of gas components in the liquid phase: $F_{j,L}^{OUT,Finisher}$

$$F_{j,L}^{OUT,Finisher} = \frac{F_{CO_2,hyd}^{OUT,Finisher}}{n_{S38,MAX}^{STORAGE} \theta_{CO_2}} \frac{1-\Phi}{\Phi} n_{water,L}^{STORAGE} x_j \quad (34)$$

Eq. 34 can be applied directly to CO₂

$$F_{CO_2,L}^{OUT,Finisher} = \frac{F_{CO_2,hyd}^{OUT,Finisher}}{n_{S38,MAX}^{STORAGE} \theta_{CO_2}} \frac{1-\Phi}{\Phi} n_{water,L}^{STORAGE} x_{CO_2} \quad (35)$$

or after summation over all the *other components*:

$$\begin{aligned} F_{other\ components,L}^{OUT,Finisher} &= \sum_{other\ components} F_{j,L}^{OUT,Finisher} \\ &= \frac{F_{CO_2,hyd}^{OUT,Finisher}}{n_{S38,MAX}^{STORAGE} \theta_{CO_2}} \frac{1-\Phi}{\Phi} n_{water,L}^{STORAGE} \sum_{other\ components} x_j \end{aligned} \quad (36)$$

In the end, the mole balance on CO₂ given in Eq.27 yields to:

$$\begin{aligned} F_{CO_2,Gas}^{OUT,Bulk} \\ - \left(1 + \frac{1}{n_{S38,MAX}^{STORAGE} \theta_{CO_2}} \frac{1-\Phi}{\Phi} n_{water,L}^{STORAGE} x_{CO_2} \right) F_{CO_2,hyd}^{OUT,Finisher} \\ = (1-RECOV) F^{dry\ flue\ gas} y_{CO_2}^{dry\ flue\ gas} \end{aligned} \quad (37)$$

And the mole balance on *other components* given in Eq.29 yields to:

$$\begin{aligned} \frac{1-y_{CO_2}^{Bulk}}{y_{CO_2}^{Bulk}} F_{CO_2,Gas}^{OUT,Bulk} \\ - \left(\frac{1-5y_{CO_2}^{OUT,TOP}}{5y_{CO_2}^{OUT,TOP}} + \frac{1}{n_{S38,MAX}^{STORAGE} \theta_{CO_2}} \frac{1-\Phi}{\Phi} n_{water,L}^{STORAGE} \sum_{other\ components} x_j \right) F_{CO_2,hyd}^{OUT,Finisher} \\ = (1-y_{CO_2}^{dry\ flue\ gas}) F^{dry\ flue\ gas} \end{aligned} \quad (38)$$

Eq.37 and Eq.38 consist of a system of two equations with two unknowns ($F_{CO_2,Gas}^{OUT,Bulk}$ and $F_{CO_2,hyd}^{OUT,Finisher}$) which can be solved analytically, provided that θ_{CO_2} and x_j are calculated elsewhere.

PARAMETRIC STUDY

The Figure 6 shows the pure CO₂ hydrate equilibrium pressure versus the temperature, given as the difference between the operative temperature and the temperature at the congruent point (10.38°C).




Figure 6: Bulk reactor operative conditions The over pressure coefficient q is given in Eq.7. The over temperature is the difference between the operative temperature and the temperature at the congruent point (10.38°C).

The bulk reactor is assumed to form a pure CO₂ hydrate because it is operating at a CO₂ molar fraction higher than 0.2 (Eq.16). The Figure 6 shows also the corresponding operative pressure in

the bulk reactor at constant $q=1.5$, (q is defined in Eq.7).

The bulk reactor pressure can not be superior to 1.5 MPa because the energy penalty for flue gas conditioning is higher than energy penalty of a MEA based capture process unit (10 points), see Figure 4.

On Figure 7, we show the liquid volume in the bulk reactor, and the bottom hydrate volume flow rate, as function of the total pressure. Both values decrease dramatically as the pressure is increased. At a pressure of 1.5 MPa, the volume of the bulk reactor is in the range of 5000-6000 m³.

The corresponding bottom hydrate flow rate is 40 m³/s, which is a very high value.




Figure 7: Bulk reactor liquid volume and hydrate bottom volume flow rate. The over pressure coefficient q is given in Eq.7.

The reason to explain such a high volume of hydrate to handle comes from the gas storage capacity of the hydrate. From paper 2 of this series, we got the Figure 8 which gives the hydrate storage capacity. At a pressure of 1.5 MPa, the solid can not store more than 500 moles of CO₂ in a volume of 1 m³, to be compared to the value of 2500 moles/m³ for an MEA Amines (Lecomte et al, 2009). More, if we assume the slurry to be concentrated at a solid fraction of $\Phi_{MAX} = 0.33$, given Eq. 14, the total bottom flow rate will be 120 m³/s, which is not realistic.




Figure 8: Storage capacity. [mole CO₂/m³ hyd] in the hydrate phase and liquid phase (from paper 2 of this series)

CONCLUSION

Experimental work has shown that it is possible (see paper 1 of this series, here **Figure 5**) to enhance the selectivity of CO₂ in the hydrate structure. The best thermodynamic additive is TBAB, a quaternary ammonium salt.

Among the additives that we tested, allowing to form a stable hydrate without gas (for example THF, cyclopentane, TBAB), it can be said that each of them can form a gas hydrate at atmospheric pressure, with an enrichment of CO₂ regarding the gas former composition. However the counterpart of the low pressure is the storage capacity that tends to vanish. From a specific thermodynamic modelling on TBAB semi-clathrate hydrate (paper 2 of this series), we proposed a correlation to calculate the storage capacity at a given operative pressure, or a given operative temperature.

In paper 3 of this series, we gave the correlations to design a bubble column running a CO₂ separation from TBAB semi-clathrate hydrate.

With a 2 stages process including a finisher, it is possible to produce pure CO₂ (this paper)


Nevertheless the volume of the reactor and the liquid flow rate handled is linked to the total pressure (**Figure 7**). The pressure can not be superior to 1.5 MPa because the energy penalty for flue gas conditioning is higher than energy penalty

of a MEA based capture process unit (10 points), see Figure 4.

The low storage capacity of TBAB semi-clathrate hydrate increases the size of the equipment and the flow rates to handle. CAPEX and OPEX for an industrial CO₂ post combustion capture unit by hydrates would be too high.

So, it appears now obvious that hydrates are not adapted for CO₂ capture in post-combustion. We need to increase the pressure to decrease the size of the capture unit which increases the energy penalty linked to flue gas conditioning.

ANNEX : FLOWSHEET



Acknowledgements:

This work has been carried out within the ANR (French Research Agency) project CO2 SECOHYA and the FP7 European project iCAP (GA n°241393).

BIBLIOGRAPHIE

Herri, J.-M., Bouchemoua, A., Kwaterski, M., Brântuas, Galfré, A., P., Bouillot, B., Douzet, J., Ouabbas, Y., Cameirao, A. 2014, Enhanced selectivity of the separation of CO₂ from NE during crystallization of semi-clathrate hydrates from quaternary ammonium, Oil and Gas, Accepted, DOI 10.2516/ogst/2013201

Lucquiaud, M., Gibbins, J., 2011, On the integration of CO₂ capture with coal-fired power plants: A methodology to assess and optimise solvent-based post-combustion capture systems, Chem. Eng. Res. Des. 89 pp. 1553–1571

Liebenthal, U.; Linnenberg, S., Oexmann, J.; Kather, A.: Derivation of correlations to evaluate the impact of retrofitted post-combustion CO₂ capture processes on steam power plant performance. International Journal of Greenhouse Gas Control, Issue 5, 1232-1239, 2011

Leconte, F., Broutin, P., Lebas, E., 2009, Le captage du CO₂, Des technologies pour réduire les émissions de gaz à effet de serre, Editions Technip

Oexmann, J.; Kather, A.; Linnenberg, S.; Liebenthal, U.: Post-Combustion CO₂ Capture: Chemical Absorption Processes in Coal-Fired Steam Power Plants. Greenhouse Gases Science and Technology, 2, 1-19, 2012.

Thambimuthu, K., Soltanieh, M., Abanades, J.C. (Coordinating Lead Authors) 2005, Capture of CO₂”, Chapter 3 in: IPCC Special Report on Carbon dioxide Capture and Storage, Cambridge University Press, UK